

DECLARATION OF PERFORMANCE

No. **EN_DOP_P75-6_C1X_Z05**

1. Unique identification code of the product-type: **Fibre-cement profiled sheet NT P75-P76 natural/coated**
2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4): **E 2200 C1X S*) DDMMYY**) NT ÜZ-31.1-175 EN13501-1A2-S1,DO**
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Roofing – Internal wall and external wall and ceiling finishes**
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

**Comptoir du Bâtiment
Heiveldekens 6B
2550 Kontich
Belgium
Manufacturing plant: 2200**

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2): **None**
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPT, Annex V: **System 3**
7. In case of the declaration of performance concerning a construction product covered by a harmonized standard: **GTC –Fire Reseach Center, Vilnius, Lithuania, No.1796;
Kiwa MPA Bautest GmbH-0770-Voltastraße5, Gebäude10.6, D-13355 Berlin, Germany;
R&D center Redco, Kuiermansstraat 1, 1880 Kapelle-op-den-Bos, Belgium;
VGTU Thermal Insulation Institute Building Material Lab, Linkmen7 g.28, LT-08217, Vilnius, Lithuania**
8. Declared performance

Essential characteristics	Performance	Harmonised technical specification
Mechanical resistance ^a	Class C1X	EN 494; 2012
Impact resistance	pass	
External fire performance	Deemed to satisfy	
Reaction to fire ^a	A2-s1,d0	
Release of dangerous substance ^a	NPD Type NT	
Water permeability	pass	
Durability against warm water	pass	
Durability soak/dry	pass	
Durability against freeze-thaw ^b	pass	
Durability against heat-rain ^b	pass	

^a Characteristics which apply to fittings. All characteristics apply to profiled sheets.

^b Characteristics which do not apply to profiled sheets for internal use

9. The performance of the product identified in point 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



Graeme Singleton

